



Technical Specifications:-

- Max. swing over bed 410mm
- Max. swing over cross slide 255mm
- Max. swing in gap 580mm
- Effective length of gap 190mm
- Width of bed 250mm
- Distance between centers 1000mm
- Center height 205mm
- Spindle nose D1-6
- Spindle bore 52mm
- Spindle taper MT6
- Range of spindle speed 16 steps 45-1800r/min
- Travel of compound rest 140mm
- Max. travel of cross slide 210mm
- Leadscrew pitch 4T.P.I.
- Max. section of tool 20×20mm
- Longitudinal feeds range 0.05-1.7mm/rev
- Cross feeds range 0.029-1.019mm/rev
- Metric threads range 42 kinds, 0.2-14mm
- Inch threads range 45 kinds, 2-72T.P.I.
- Diametrical pitches range 21 kinds 8-44D.P.
- Module pitches range 18 kinds, 0.3-3.5M.P.
- Tailstock quill diameter 50mm
- Tailstock quill travel 120mm
- Tailstock quill taper MT4

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

- Main motor power 2.2kw
- Coolant pump motor 120w
- Overall dimension 1940/2440×850×1300mm
- Packing size 2060/2560×900×1640mm
- N.w/G.w 1500/1750kg, 1550/1800kg

Accessories :

- Brake
- Coolant system
- Working lamp
- Single point Cutting tools (5 Pcs.) HSS
- Tool set
- Operation manual
- Warranty: 1 (One) year

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com