

**Tehnical Specifications:**

- Three Speed Load Frame, 50kn (5000 Kgf) Capacity
- Mould 150mm Id X 175mm Hight.
- Penetration Piston, 50mm Face Dia.
- Adjustable Bracket, for Penetration Dial Gauge
- Circular Metal Spacer Disc. with Detachable Handle
- 148mm Dia X 47.7mm Hight
- Annular Metal Weight, 2.5Kg, 147mm Dia with 53 mm Dia Central Hole
- Perforated Metal Weight 2.5 Kg. 147mm Dia, with 53mm Dia Soft
- Perforated Plate, 148mm Dia, with Adjustable Stem and Lock Nut
- Metal Tripod for Dial Gauge
- Cutting Collar
- Rammer 2.6Kg, 310mm Controlled Drop
- Rammer 4.9Kg, 450mm Controlled Drop
- S Type Load Cell Capacity 50 kN
- LVDT, 25 mm Travel, 0.01mm Lea

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com