



### Key Features:

- R.S. Flip-Flop without clock.
- R.S. Flip-Flop with clock.
- D Flip-Flop.
- J-K Flip-Flop.
- T Flip-Flop.
- Master Slave J-K Flip-Flop.

### TECHNICAL PARAMETERS

#### Power Supplies:

- DC Power Supply +5V,150mA
- Operated on Mains power 230V, 50Hz +10%

#### Technical specifications:

- Four independent logic level inputs to select High / Low TTL levels, each with a LED to indicate high / low status and termination.
- Two independent buffered logic level indicators for High / Low status
- A Pulser to provide the pulses manually for triggering.
- One 7473IC provided on board for JK and T type Flip Flop.
- One 7474 IC Provided on the board for D Type Flip Flop
- One RS Flip Flop Circuit is provided on Board using TTL Gate.
- One JK Master Slave Flip Flop is provided on Board using TTL Gate.

#### SALIENT FEATURES:

- Front panel built with high class insulated Printed Circuit Board sheet with well printed circuits and symbols.
- Instruction manual.
- Connections are brought out through 2mm Colored Sockets.
- Patch Cords 2mm.
- The trainer is housed in ABS Plastic cabinet/Wooden.
- Size of the trainer set 12"x8"

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com