

**Application/Test facility:**

- Demonstrates the principle and operation of a strain gauge, with tare adjustment, digital readout, and an ergonomic powder-coated cabinet featuring an acrylic front panel.

Product Features:

- Self-contained and easy to operate
- Sensitive, Linear, Stable & Accurate
- Test-points to observe input output of each block
- Onboard gain adjustment
- Onboard offset null adjustment
- Built in DC Power Supplies
- 3½ digits LED display
- Onboard Cantilever arrangement
- High repeatability and reliability
- Strain Gauge (350Ω): 4 nos. or more
- Gauge factor: 2.1
- Maximum bearable weight: 500 gm
- Cantilever material: Stainless Steel or better
- Cantilever width: at least 2.5 cm
- Cantilever thickness: at least 0.16 cm
- Cantilever length: at least 20 cm
- Bridge Voltage: +8 V DC
- Bridge configuration: Full Bridge
- Test points: minimum 8 nos.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

Accessories/Spares:

- Mains cord
- Standard Weights
- USB cable (optional)



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com