

S. No.	Order Code	Description of Goods	Offered Specification	Image
1	23246945.1	Tape meter	Rienforcing steel	
2	23246945.2	Iron Wooden Handle Garden Spade	Maintenance kit	
3	23246945.3	LM7806 IC - 6V Positive Voltage Regulator IC + 9-0-9 transformer + Diode bridge and other components	• Voltage Regulator IC, components:-Transformer (230V Primary 9V Secondary), Diode (2AmpsBridge), 1(470uF), c2, c3 (0.01uF)	
4	23246945.4	Portable digital balance	Portable digital balance , Chargeable	
6	23246945.6	Spin Coating Unit	User Profiles 10 Programs 10 programs on each user profile, with up to 50 steps each Speed stability <2% error Speed 120 to 6000 RPM Spin time 1 – 1000 sec	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.







Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

			<p>Power supply DC 24 V 2 A, via 100–240 V 50/60 Hz power adapter Safety Switch Magnetic safety switch on the door Dimensions (D x W x H) 225 mm x 170 mm x 140 mm (8.86" x 6.69" x 5.51") Materials Polypropylene bowl, steel casing, tempered glass lid</p>	
12	23246945.12	Light Sensitive Photoresistor LDR	" • LDR light sensor (Light Dependent Resistor or photo resistor)"	
13	23246945.13	Vacuum Pump	vacuum pump for filtration, Millipore, Chemical Duty Pump, 220 V/50 Hz	
15	23246945.15	Stainless Steel Angle Valve	Rienforcing steel	
16	23246945.16	Mild Steel plate (100x100x20)	Steel plate for rammer making (100x100x20)	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

17	23246945.17	SeedStudio Base Shield V2	<ul style="list-style-type: none"> Compatible with Arduino range of products Supports 5.0V and 3.3V 12 Grove Connectors on Board Solid Physical Connection 	
18	23246945.18	210PC Mixed Tool Set	<ul style="list-style-type: none"> 210 Piece Socket Wrench Auto Repair Tool Combination Package Mixed Tool Set Hand Tool Kit with Plastic Toolbox Storage Case 	
19	23246945.19	Digital Automatic Seed Counter Machine	<p>Automatic Seed Counter machine, Suitable for corn, rice, wheat, rape, vegetables and other seeds. automatic sample separation function</p> <p>Maximum speed of 1000 to 2000 particles/minute</p> <p>Counting range 1~9999</p> <p>Record content: time, total number of grains, and number of samples.</p> <p>Adjustable speed: Turntable operation: automatic, jog, manual</p>	
22	23246945.22	58 in 1 Screwdriver Tool Set,	<ul style="list-style-type: none"> Precision Screwdriver Set with 56 Bits, 58 in 1 Professional Repair Tool Kit with Flexible Shaft 	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.




Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

23	23246945.23	Painter Spray Gun Popular Paint Spray Gun. (PR-01, 1.4 mm)	Operating pressure : 40 – 60 psi, paint capacity : 550 ml Nozzle size : 1.4 mm, feed : gravity Gun distance : 9 inch, air consumption : 225-300 (ltr/min) Material output : 325 (ltr/min), weight : 700 gm Separate and adjustable fluid , fan pattern and air controls for precise application	
24	23246945.24	100 PPR 2-Phase Incremental Optical Rotary Encoder	"Encoder Type Incremental Operating Voltage (VDC) 5 ~ 24 Current Consumption (mA) ≤40 Maximum Speed 5000 RPM Pulse Per Revolution (PPR) 100 Counts Per Revolution (CPR) 400 Operating Temperature Range (°C) : -24 to 84 Output Phase : AB Protection Standard : IP52 Cable Length (Meter) 1.5 Body Dimensions (Dia. x Length) mm : 40 x 38.40 Shaft Type D-type, Solid	
25	23246945.25	Pressure sensor	Interface Type : Serial Data Output Rate: 10 SPS / 80SPS Max. Operating Current (mA) : 1.5 Operating Temperature Range (°C) :-40 to 85 IC Package :16 Pin SOP Gain: 32 / 64 / 128"	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

26	23246945.26	Motion sensor	" • Feature: Shall incorporate: gyroscope, accelerometer, magnetometer and barometer"	
27	23246945.27	Peg Board Tool Holder Set includes screws and wall plugs	• Element System Peg Board Tool Holder Set includes screws and wall plugs - White	
28	23246945.28	Toolboard		
29	23246945.29	Large Wooden Mallet Hammer		
31	23246945.31	Mild Steel Self Sharpening Sickle		

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

32	23246945.32	Ultrasonic Distance sensor	<ul style="list-style-type: none"> Provides precise, non-contact distance measurements within a 2 cm to 3 m range 	
34	23246945.34	PH-700 Digital pH Meter with Temperature measurement and user-calibratable	<p>pH Range: 0 - 14 Temperature Range: 1-80 °C; 33-176 °F Resolution: 0.1 pH; Temperature resolution is 0.1 °C/°F Accuracy: +/- 0.2 pH; Temperature accuracy is +/- 2% Calibration: Digital automatic calibration (one point) Electrode: Glass sensor and reference tube electrodes Housing: Water resistant Power source: 3 x 1.5V button cell batteries (model 357A; included) Dimensions: 15.3 x 3.2 x 1.8 cm (6.0 x 1.3 x 0.7 inches) Weight: 53.9 g</p>	
35	23246945.35	PH Sensor	<p>"• Module Power: 5 V • PH Measuring Range: 0-14 • Accuracy varies with only +/-0.1 pH (25 degree Celsius) • Response time is less than 1 min Has a BNC connector to connect pH sensor • Power indicator LED Gain Adjustment Potentiometer"</p>	
36	23246945.34	TMT Reinforced Steel Bars	Reinforced steel bar for rammer making	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

37	23246945.37	PLA+ 1.75mm 3D Printing Filament 1kg-Black	1.75mm PLA filament. 750-1000 g spools	
38	23246945.38	Brass Gate Valve, Valve Size: 3/4 Inch		
39	23246945.39	GoPro Hero9	<p>"Sensor Type CMOS Sensor Sensor Resolution Effective: 23.6 Megapixel Recording Media/Memory Card Slot Single Slot: microSD/microSDHC/micro SDXC Video Format 5120 x 2880 at 24/25/30 fps (100 Mb/s MP4 via H.264/AVC, H.265/HEVC) 4096 x 3072 at 24/25/30 fps (100 Mb/s MP4 via H.264/AVC, H.265/HEVC) 3840 x 2160 at 24/25/30/50/60 fps (100 Mb/s MP4 via H.264/AVC, H.265/HEVC) 2704 x 2028 at 50/60 fps (100 Mb/s MP4 via H.264/AVC, H.265/HEVC) 2704 x 1520 at 50/60/100/120 fps (100 Mb/s MP4 via H.264/AVC, H.265/HEVC) 1920 x 1440p at 24/25/30/50/60/100/120 fps (MP4 via H.264/AVC, H.265/HEVC) 1920 x 1080p at 24/25/30/50/60/100/120/200 /240 fps (MP4 via H.264/AVC, H.265/HEVC) Still Image Support JPEG</p>	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

			<p>20 MP Audio Format WAV Display Display Type Fixed Touchscreen LCD Size 2.27" Secondary Display Front: Live-View Monitor Exposure Control Shutter Speed 1/25 - 1/2000 Seconds (Photo) ISO Sensitivity Photo/Video: 100 to 6400 Burst Photo 30 Photos / 3 Seconds Features Image Stabilization Digital Waterproof Depth Rating 33.0' / 10.0 m (Camera) White Balance Modes Auto Built-In Mic Yes Built-In Speaker Yes Wi-Fi Yes Input/Output Connectors Outputs 1 x USB 3.0 Type- C General Battery Rechargeable Battery Pack, 1720 mAh Charging Method USB Dimensions (W x H x D) 2.8 x 2.2 x 1.3" / 71.0 x 55.0 x 33.6 mm Weight 5.6 oz / 158 g "</p>	
41	23246945.41	Temperature sensor"	<p>Input: thermal resistance Pt100, Cu50, Cu100(two- wire/three-wire/four-wire) Thermocouple K, E, S, B, T, J, N(two-wire) Intelligent input signal and range can be set by PC or hand controller. Output: the output of 4~20mA dc signal within the range can be linear with the output resistance signal of the thermal resistance thermometer and the input temperature signal of the thermal resistance thermometer; Linear with the input millivolt signal of the thermocouple or with the input temperature signal</p>	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

			of the thermocouple thermometer.	
42	23246945.42	Flex sensors	"• Operating voltage of FLEX SENSOR: 0-5V • Can operate on LOW voltages • Power rating : 0.5Watt (continuous), 1 Watt (peak) • Life: 1 million • Operating temperature: -45°C to +80°C • Flat Resistance: 25K Ω • Resistance Tolerance: ±30% • Bend Resistance Range: 45K to 125K Ohms(depending on bend)"	
43	23246945.43	Ultrasonic Sensor	Operating Voltage (VDC): 2.4 to 5 Frequency(Hz): 40000 Average Current Consumption (mA) :2 Max. Sensing Distance (cm): 450 Sensing Angle: 15° Sensor Cover Dia. (mm): 16	
44	23246945.44	Door Key	Cement, Paint, others	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

45	23246945.45	Moisture sensor	Operating voltage: 3.3v-5v Use chip lm393 Pcb size: 3.2cm x 14cm	
46	23246945.46	High Tempered Iron Pickaxe		
48	23246945.48	3D Handheld Laser Scanner	Accuracy :0.05mm Resolution : 0.1 – 0.2 mm Detecting Range : 200x100mm Working Distance : 150-400mm Scanning range(°): 15x15x15mm Light Source : LED+NIR Output Formats: OBJ/STL/PLY Speed : 10 fps Length (mm) :155 Width (mm): 84 Height (mm) : 46 Weight (gm): 370 Shipping Weight ; 2.03kg Shipping Dimensions : 35 ×27 ×12 cm	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com