



SPECIFICATIONS:-

Frequency(GHz)	DC-2.5	
Insertion Loss(dB)	≤3.0	
VSWR	≤1.4	
Attenuation range(dB)	0-90	
One-button accuracy(dB)	1dB button	±0.2dB &DC-1GHz
	2dB button	±0.3dB &DC-1GHz
	4dB button	±0.4dB &DC-1GHz
	8dB button	±0.7dB &DC-1GHz
	16dB button	±1.0dB &DC-1GHz
	20dB button	±1.2dB &DC-1GHz
Repeated addition accuracy(dB)	≤10dB	≤0.7dB &DC-1GHz
	≤60dB	≤1.2dB &DC-1GHz
	≤90dB	≤2.5dB &DC-2.5GHz
Impedance (ohm)	50	
Connector	N-F/SMA-F	
Operating temprature (°C)	-40~+50	
Dimensions (mm)	164mm *36mm*20 mm	
Weight (kg)	0.15	
Weight (kg)	10W	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com