

**Specifications :**

- Minimum working force 500 kn;
- Minimum folding length 2000 mm;
- Minimum distance between uprights 1000 mm;
- Gooseneck depth 315 mm;
- Minimum power 4 kw;
- Three-phase power supply 380 - 400 v - 50 hz;
- Manual adjustment of slide stroke and pressure;
- Pedal control of slide movements;
- Complies with work safety standards.

Tools included:

- 1/10th rear stop;
- 2 tilting stops;
- 2 sliding stops;
- Micrometric;
- Front arm;
- Tilting slide and stop.

Punches included:

- Standard punch at 88° length 415 mm;
- Standard 88° split punch with right and left horns,
- Total length 835 mm;

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Heavy punch at 60° length 415 mm;
- Radius punch r.20 length 835 mm;
- Radius punch r.20 length 415 mm.
- With necessary accessories and fixing elements for the proper functioning of the machine.

25268523G.4A : 400 ltr Hyd.oil for hydraulic Press Brake (25268523G.4)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com