

**Technical Specifications:-**

- Following Features should have available: Rapid , Accurate , and Stable Automatic Compensation. Ultra-Short 20cm (7.9 in.) Focusing. All-Weather Dependability. Clamp less , Endless Fine Horizontal Adjustments. , Main Technical parameter: Telescope: Length: Min. 215Mm, Magnification: Min. 32x , Objective Aperture: Min. 42mm , Resolving Power: Min. 3 Inch, Field of View (at 100m): Min. 1°20 feet, Minimum Focus: 0.2m from end of telescope, Stadia Ratio: 100, Focusing Knob: 2-speed, Sighting Aid: Peep Sight, Accuracy (1km double run levelling): Max. 0.7mm , Compensator: , Type: Pendulum compensator with magnetic damping system, Working Range: Max. ±15 feet , Circular Level Sensitivity: Min. 10 feet/2mm, Horizontal Circle Division: 1°/1gon , Water Resistance: IPX6 , Following accessories should be supplied: Levelling staff 5m , 5 Section with circular bubble-01 No.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com