



**Ref. Image**

### Key Features

- ProgrammableLogicController(PLC) Digital input:12 nos.
- Digitaloutput:8 nos. Analog input:4 nos. Analogoutput:2 nos.
- Programsize:4096(inwords) Communication: USB Expansion: Yes  
HumanMachineInterface(HMI)HMI Supply: +24V DC
- CPU:32-bits400MHz
- RISCInterface:RS485 Storage Flash:128MB DDRAM:64MB
- Display size:7inch
- Resolution:800×480TFTLCD65,536 colors
- Touchscreen:Highprecisionfour- wire resistive

### General Specification

- Toggle switches: 4 nos.
- PushtoONswitches:3nos
- Proximitysensor:1no.
- Selector switch: 1no.
- Visualindicators:4nos.
- Audio indicator:1 Nos
- DC Motor:1 no.

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

- Relaycard:1no.(Contains2relays)
- Voltage display:1 no.
- Contactor:1 no
- PLCsoftware: Appropriate HMI software:
- Appropriate Accessories:
- Mains cord :1 no.
- Serial to USB :1no
- (convertor) : USB
- cable(AtoB) :1 no.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com