



### **Techincal Specifications :**

#### **1. Siemens Motor Starter Protector, Screw Connection :-**

- MPCB Overload Range: 13 - 20 A
- MPCB Rated Current: 20 A
- Product Type: Protection Circuit Breakers
- Size of MPCB: S0
- Terminal: Screw

#### **2. Transverse Auxiliary Switch 1 NO + 1 NC, Screw Type :-**

- Size of the circuit-breaker S00, S0, S2, S3
- Protection class IP on the front IP20
- Width : 45 mm
- Height : 12 mm
- Depth : 17 mm
- Operating current:

at AC-12

- at 24 V : 2.5

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



- at 230 V : 2.5
- maximum : 10

at AC-15

- at 24 V : 2
- at 230 V : 0.5

at DC-13

- at 24 V : 1
- at 48 V : 0.3
- at 60 V : 0.15

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com