



Key Specifications:

- **Output Voltage (Low Range):** 220–240 V (Manual Hand Crank)
- **Output Voltage (High Range):** Up to 100 kV (via integrated step-up mechanism)
- **Crank Mechanism:** Heavy-duty manual hand crank for reliable voltage generation
- **Base Dimensions:** 6" x 8" (152 mm x 203 mm)
- **Overall Height:** Approx. 22" (559 mm)
- **Mounting:** Both major components are securely mounted on a rigid base platform for operational stability

Construction & Features:

- **Base:**
Durable, compact 6" x 8" base plate designed for sturdy benchtop use.
- **Mounting:**
All components are securely fixed to the base to minimize vibration and ensure safe operation.
- **Height:**

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

Approximate overall height of the assembled unit is 22", allowing for easy crank access and visibility during operation.

- **Design Purpose:**

Engineered for educational demonstrations, testing environments, or light-duty laboratory applications requiring high-voltage generation from a manual source.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com