



SPECIFICATIONS:

Resistive Load Bank

Rated Capacity:

- 500 kW

Electrical Specifications:

- Input Voltage: 415 V AC
- Rated Current: 700 A
- Frequency: 50 Hz

Protection & Switching:

- Main Incomer: 1 × MCCB, 700 A
- Load Step Control: 7 × MCCBs, 100 A each

Load Elements:

- Fixed resistance tubular elements
- High-grade alloy resistance tubes
- Fully factory-fitted and pre-wired

Cooling System:

- Forced air cooling with high-efficiency cooling fans
- Vertical airflow design with upward air discharge
- Weather canopy provided for protection

Mechanical Construction:

- Robust fabricated steel enclosure
- Mounted on heavy-duty wheels for mobility

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com



- Integrated towing (TUG) arrangement for easy pulling and positioning

Application:

- Suitable for testing generators, UPS systems, transformers, and power sources under full load conditions



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com