

Order Code : 20213590.1.16
Name : Relay and substation tester



Specifications are valid for resistive load, at 170-240 voltage supply and ambient temperature $+25^{\circ}\text{C} \pm 3^{\circ}\text{C}$, ($77^{\circ}\text{F} \pm 5.4^{\circ}\text{F}$) after 30 minutes warm up time and in the frequency range 10 Hz to 70 Hz. All hardware data are for full scale values. Specifications are subject to change without notice.

Environment

Application field: For use in high-voltage substations and industrial environments.

Temperature:

Operating	0°C to +50°C (32°F to +122°F)
Storage & transport	-40°C to +70°C (-40°F to +158°F)
Humidity	5% – 95% RH, non-condensing
Altitude (operational)	2000 m (6500 ft)
Shock and vibration	IEC 60068-2-27
Vibration	IEC 60068-2-6
CE-marking	
EMC	IEC61326 -1
LVD	IEC61010-1:2010

General

Mains input	100 - 240 V AC, 50 / 60 Hz
Current consumption	10 A (max)
Power consumption	1800 VA (max)
Dimensions	
Instrument	350 x 270 x 220 mm (13.8" x 10.6" x 8.7")
Flight case with wheels	615 x 295 x 500 mm (24.2" x 11.6" x 19.7")
Flight case	620 x 295 x 365 mm (24.4" x 11.6" x 14.4")
Weight	14.9 kg (32.8 lbs) Instrument only
	29.0 kg (64 lbs) with accessories and
flight case (with wheels, GD-00185)	23.9 kg (52.7 lbs) with accessories and
flight case (GD-00182)	
Display	5.7" LCD Touch screen
Available languages	Czech, English, French, German, Spanish, Swedish

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

TESCA TECHNOLOGIES PVT. LTD.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302029, Rajasthan, India.
Ph/ Fax: 91-141-2771791, 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in