

Technical Specifications

- **Techniques Supported:** PCM, DPCM, CVSD
- **Crystal Frequency:** 7 MHz or higher
- **Signal Generators (On-board):**
 - Waveforms: Sine, Square, Triangle, Arbitrary
 - Frequencies: 500 Hz, 1 kHz, 2 kHz, 3 kHz
- **Transmission Effects:** Attenuation (7 dB & 10 dB), Noise, Filter
- **Sampling Frequencies:** 4 kHz, 8 kHz, 16 kHz, 32 kHz
- **Line Speed Options:** 32 kHz, 64 kHz, 128 kHz, 256 kHz
- **Selection Mode:** Push switches
- **Low-Pass Filter:** 2nd order Butterworth, Cut-off at 5 kHz
- **Test Points:** More than 35 accessible points
- **Interconnections:** 2 mm sockets

Accessories / Spares

- Coaxial cables and patch cords
- Speaker unit
- Oscilloscope probes

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com