



Key Features:

- Multiplexer
- 1:8 Demultiplexer
- 4:1 Multiplexer
- 4:1 Demultiplexer

TECHNICAL PARAMETERS

Power Supplies:

- DC Power Supply +5V,150mA
- Operated on Mains power 230V, 50Hz $\pm 10\%$

Technical specifications:

- Twenty One independent logic level inputs to select High /Low TTL levels, each with a LED to indicate high / low status and termination.
- 8 independent buffered logic level indicators for High /Low status
- And gate operation given onboard.
- IC for Multiplexing 74151 and 74153 is provided on board with Combinational Circuit.
- IC for Demultiplexing 74139 and 74138 is provided on board with Combinational Circuit.

SALIENT FEATURES:

- Front panel built with high class insulated Printed Circuit Board sheet with well printed circuits and symbols.
- Instruction manual.
- Connections are brought out through 2mm Sockets.
- Patch Cords 2mm.
- The trainer is housed in ABS Plastic cabinet.
- Size of the trainer set 12"x8"

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com