

**Description:**

A robust and versatile power supply unit designed for laboratory and industrial applications, offering both AC and DC outputs with continuous variability. The unit is fully protected against overloads and short circuits, ensuring safe and reliable operation under demanding conditions.

**Technical Specifications:**

- **Mains Supply:** 240 V AC, 50 Hz, single-phase
- **Output Voltage (AC):** 0 – 24 V, continuously variable
- **Output Current (AC):** 0 – 8 A
- **Output Voltage (DC):** 0 – 24 V, continuously variable
- **Output Current (DC):** 0 – 8 A
- **Isolation:** Outputs fully isolated from mains supply
- **Output Connection:** 4 mm safety sockets
- **Operation:** Ranges selectable under full load conditions
- **Protection:** Overload and short-circuit protected
- **Metering:** Digital voltmeter included for precise monitoring

**Supplied Accessories:**

- PVC insulated and sheathed mains cable
- 13 A sleeved plug to BS1363/A (fitted)
- Service manual and instruction manual (English)

**Compliance & Safety:**

- Fully CE marked, complying with the latest EC safety standards
- Manufacturer's Statement of Compliance provided

**Applications:**

- Educational laboratories
- Research facilities
- Industrial testing and training setups

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com