



Diaphragm type Vacuum pumps & Compressor which are manufactured from special grade aluminium for light weight and good strength. Diaphragms are made of 2 - ply nylon/PTFE reinforced neoprene, Viton rubber. Valves are SS316 while special sealed bearings are used hence no lubrications is required.

Unique Features

- Noiseless performance
- Absolutely portable
- Totally oil-free construction
- Practically maintenance-free
- Built-in micro suction filter
- Special diaphragms available (TEFLON / VITON, etc.)
- Extra-large bearings for trouble-free and smooth operation
- Chemical-resistant models available with contact parts in PP / PVC / TEFLON / SS (Model: TL-XX-CRP)
- Motors available in both single-phase and three-phase configurations

Application Areas

- Biology laboratories
- Food industry
- Microbiological detection
- Vacuum extraction
- Liquid filtration
- Vacuum drying
- Suspended solids measurement

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Pharmaceutical and chemical industry

Technical Specifications :

- Max. Vacuum: 27" Hg
- **Max. Flow Rate:** 25 L/min
- **Max. Pressure:** 35 psig
- **Motor Power:** 1/6 HP
- **Weight:** 4.1 kg
- **Noise Level:** 50 dB
- **Power:** 75 W
- **Power Input:** 220V / 50Hz

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com