

Order Code : 20213572.1

Name : Optical light source VTC 230S



### Specifications:

- Provides 2 output wavelengths which can be optional according to customers needs CW, 2Hz modulation output at 650nm, and CW, 270Hz,1KHz,2KHz modulation output at other wavelengths.
- High stability of the output power
- Stable output wavelength
- Backlight LCD display supports night operation
- Compact size and decent appearance
- Large LCD, easy operation

### Applications

- Maintenance in Telecom Maintenance CATV
- Test Lab of optical fibers
- Other Fiber Optic Measurements

Wavelengths(nm)	1310/1550nm
Emitter Type	FP-LD,LED or others please specify
Output Power(dBm)	-6~-7(1310/1550nm),>0 (650nm)
Spectral Width(nm)	
Output Stability	+0.05dB/15mins; +0.1dB/ 8hours
Modulation Frequencies	CW / 2(650nm) / 270, 1K,2K (1310nm/1550nm)
Optical Connector	FC/PC ( Interchangeable FC/SC/ST connectors can be optional)
Power Supply	Alkaline Battery(3 AA 1.5V batteries) optional
Battery Operating Time(hour)	45
Operating Temperature(oC)	_ 10 ~ +60
Storage Temperature(oC)	_ 25 ~ +70
Dimension(mm)	172*82*33
Weight	295g

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

### **TESCA TECHNOLOGIES PVT. LTD.**

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302029, Rajasthan, India.  
Ph/ Fax: 91-141-2771791, 2771792; Email: [info@tesca.in](mailto:info@tesca.in), [tesca.technologies@gmail.com](mailto:tesca.technologies@gmail.com)  
Website: [www.tesca.in](http://www.tesca.in)