



## SPECIFICATIONS

### WORKING AREA

- Table dimensions – 600 mm x 300 mm
- Table load capacity 150 kg
- Number of T-slots 3 positions
- T-slots, width 14 mm
- T-slots, spacing 100 mm
- Spindle nose-to-table surface distance 100 mm - 580 mm

### TRAVELS

- Travel X-axis 400 mm
- Travel Y-axis 230 mm
- Travel Z-axis 450 mm
- HEAD STOCK
- Spindle speed 8000 1/min

### FEED

- Rapid feed X-axis 12000 mm/min
- Rapid feed Y-axis 12000 mm/min
- Rapid feed Z-axis 10000 mm/min
- Work feed X-axis 1 mm/min - 10000 mm/min
- Work feed Y-axis 1 mm/min - 10000 mm/min
- Work feed Z-axis 1 mm/min - 10000 mm/min

### TOOLING

- Number of tool stations 12 positions
- Tool Ø 100 (130) mm
- Tool length (max.) 300 mm
- Tool weight max. 8 kg
- Tool-change time tool/tool 7 sec
- DRIVE CAPACITY
- Motor rating main drive 3,7 kW
- Motor rating X-axis 0,75 kW
- Motor rating Y-axis 0,75 kW
- Motor rating Z-axis 1 kW
- MEASURES AND WEIGHTS
- Overall dimensions (length x width x height) 2.1 m x 1.9 m x 2.45 m
- Weight 2200 kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com