


Specifications :

Power/Cylinder	40 HP/3
Type	Diesel,4 stroke - DI
Bore/Stroke (mm)	105*120
Engine Capacity(CC)	3120
Rated Engine RPM	2000
HYDRAULIC	
Hydraulic Pump	Gear Type
Hydraulic Capacity(Kg)	1800
Control	Position,Draft & Mix Control
Steering	Power Steering
Turning Radius	3.1m,3m(On Brake)
Front Axle Beam	Adjustable
P.T.O	
6	6
540 Optional:Reverse PTO	540 Optional:Reverse PTO
34.3 KW/2200	34.3 KW/2200

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

CLUTCH	
Type	Double Dry Clutch
Plate Size	280 mm
FILLING CAPACITY(LITRE)	
Diesel	Tank 55
Engine Sump	8
Transmission	55
Cooling System	Water Cooled
Air Cleaner	Dry Air Cleaner
Fuel SUMP	In Line (Bosch)
Brake	Oil Immersed/Disc Brake
Electric Power	12V,88 amp
Alternator	12v ,35 amp
TYRE SIZE	
Front	6.00*16/7.50*16
Rear	14.9*28/16.9*28

GEAR BOX	GEAR	LO	HI
	1 st	2.14	8.87
	2nd	2.71	11.22
	3rd	4.51	18.64
	4rd	7.83	32.38
	R	3	12.42

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com