



Technical Specifications

Capacity	Max swing over bed	500mm
	Max swing over cross slide	330mm
	Max swing over gap	660mm
	Effective length of gap	200mm
	Center Distance	1500mm
	Bed width	360mm
Head Stock	Spindle bore	80 mm
	Spindle nose	ISO-C6
	Spindle taper	MT6
	Spindle speed (Number)	(9steps)40-1400rpm
Feeds	Longitudinal metric feed	25kinds0.021-0.592mm/rev
	Cross metric feed	25kinds0.015-0.432mm/rev
	Metric threads range	17Kinds0.25-7mm
	Inch threads range	30Kinds 5-144T.P.I
	Moudle thread Range	17Kinds0.25-3.5M.P
Carriage	Max travel of top slide	95mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com



	Max travel of cross slide	250mm
	Max size of toolshank	20*20m ²
Tailstock	Dia of tailstock sleeve	65mm
	Taper of tailstock sleeve	MT4
	Max travel of tailstock	140mm
Motor	Main drive motor	5.5KW
	Coolant pump motor	90W
	Rapid travel motor	125W
Packing	Center Distance(100mm)	292*112*178cm
Weight	Center Distance(1000mm)	1750/2050kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

