



TECHNICAL SPECIFICATIONS

- Ammeter 2Ma/200mA DC.
- Voltmeter/ Ammeter 20V/20mA
- Voltmeter 2V/200V DC.
- Operated on Mains power 230V, 50Hz $\pm 10\%$
- DC Power Supplies IC Regulated 0-15V, 500mA
- DC Power Supplies IC Regulated 0-30V, 500mA
- DC Power Supplies Fixed $\pm 12V$, 500mA
- DC Power Supplies Fixed $\pm 5V$, 500mA
- AC Power Supplies Isolated 15-0-15V, 500mA
- AC Power Supplies Isolated 9-0-9V, 500mA
- 0-100KHz Function Generator (Sine, Square, Triangle)
- 0-10KHz Function Generator (Sine, Square, Triangle)
- Variable Resistor (1K, 10K, 100K)
- Buzzer as Continuity Tester
- Low Frequency Speaker.
- SPDT Switched
- 2 Nos. Bread Board provided with module box

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com