

**Specifications:**

- The CBR Load Frame Consists of :Load Frame, 50kn (5000 kgf) Capacity,
- 3 Speeds Zinc Coated Mild Steel Mould 150mm ID x 175mm high
- Perforated Base Plate for ZI3074- 2 Zinc Coated Mild Steel Mould
- Zinc Coated Mild Steel Extension Collar, 150mm ID x 50mm high
- Penetration Piston, 50mm face dia
- Adjustable Bracket, for Penetration Dial Gauge
- Circular Metal Spacer Disc. With detachable handle, 148 mm dia x 47.7 mm high time.
- Annular Metal Weight, 2.5kg, 147mm dia with 53 mm dia central hole
- Perforated Metal Weight 2.5 kg. 147mm dia, with 53mm dia soft
- Perforated Plate, 148mm dia, with adjustable stem and lock nut
- Metal Tripod for Dial Gauge
- Cutting Collar
- Rammer 2.6kg, 310mm controlled drop
- Rammer 4.9kg, 450mm controlled drop
- Proving Ring Capacity 50 KN
- Dial Gauge, 25 mm travel, 0.01mm least count
- Optional Extras: Annular Metal Weight 5 kg, 147mm dia with 53 mm dia central hole
- Slotted Metal Weight 5 kg 147mm dia with 53mm dia slot
- Power Source
- 220 V,50 Hz AC Supply
- Finishing: Polished Material

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com