


3 5/6 digit 6000 counts Trms AC / DC Auto Ranging,  
 Data Hold, APO, Backlight Temperature, Frequency,  
 Capacitance Diode, Continuity, Resistance Check

<b>Ranges</b>	
<b>DC Voltage</b>	<b>6V/60V/600V</b>
Accuracy	± (0.8%+3dgts) on 6V - 60V ± (1.0%+5dgts) on 600V
<b>AC Voltage</b>	<b>6V/60V/600V</b>
Accuracy	± (1.5%+5dgts) on all ranges
<b>DC Current</b>	<b>60A/600A</b>
Accuracy	± (2.5%+5dgts) on 60A ± (2.5%+8dgts) on 600A
AC Current	60A/600A
Accuracy	±(2.5%+5dgts) on 60A ±(2.5%+8dgts) on 600A
<b>Resistance</b>	<b>600Ω/6KΩ/60KΩ/600KΩ/ 6MΩ/60MΩ</b>
Accuracy	± (1.0%+3dgts) on 600Ω - 6MΩ ± (1.5%+3dgts) on 60MΩ
<b>Capacitance</b>	<b>60nF/600nF/6μF/60μF/ 600μF/1000μF</b>
Accuracy	± (3.0%+18dgts) on 10nF ± (1.0%+3dgts) on 100nF - 1000μF
<b>Temperature</b>	<b>0°C - 600°C / 32°F-1112°F</b>
Accuracy	± (1.0%+3dgts)
<b>Frequency</b>	<b>10Hz/100Hz/1KHz/100KHz/ 1MHz/10MHz</b>
Accuracy	± (0.8%+3dgts) on all ranges
<b>Jaw Size</b>	28mm
<b>Power</b>	AAA 1.5V (2 Batteries)
<b>Low Battery</b>	"  " is indicated
<b>Dimensions</b>	185 x 90 x 35mm (approx.)
<b>Weight</b>	160gms. Incl. Battery (approx.)
<b>Accessories</b>	Test Leads, Carrying Case Operational Manual K-Type Thermocouple Leads



Note: Specifications are subject to change.