

**Description:**

A compact, durable, and user-friendly DC power supply designed for laboratory and educational use. It provides stable, switchable low-voltage outputs with built-in protection features, ensuring safe operation under all load conditions.

**Technical Specifications:**

- **Mains Supply:** 240 V AC, 50 Hz, single-phase
- **Output Voltage (DC):** 0 – 12 V, switchable in **1 V or 1.5 V steps**
- **Output Current (DC):** 0 – 3 A
- **Isolation:** Outputs fully isolated from mains supply
- **Output Connection:** 4 mm safety sockets
- **Operation:** Voltage ranges selectable while under full load
- **Protection:**
  - Overload protected
  - Overheating protected
  - Short-circuit protected

**Design Features:**

- Integrated **carrying handle** for portability
- Rugged construction for long service life

**Supplied Accessories:**

- PVC insulated and sheathed mains cable
- 13 A sleeved plug to BS1363/A (fitted)
- Service and instruction manuals (English)

**Compliance & Safety:**

- Fully CE marked, in compliance with latest EC safety standards

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



- Manufacturer's **Statement of Compliance** provided

**Applications:**

- Educational laboratories
- Physics and electronics training
- General low-voltage DC experiments and testing



*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

