

**Specifications -**

- 1 - High precision gas adsorption for surface area and porosity measurements;
- 2 - Analyze range:  $1.3 \times 10^{-9}$  to  $1.0 \text{ P/P0}$   $1 \times 10^{-6}$  to 900 torr;
- 3 - Available Micropore Ports: up to 3, one port dual purpose chemisorption and physisorption;
- 4 - Dosing and Evacuation Control: Proprietary Servo proprietary Servo;
- 5 - Roughing Pump: 4 stage diaphragm 4 stage diaphragm;
- 6 - Krypton Analysis: Standard 1 port, optional up to 3 ports Standard 1 port, optional up to 3 ports;
- 7 - Analysis Gas Per Sample: Ability to use up to 3 gases concurrently, one probe gas on each port;
- 8 - Minimum Measurable Surface Area: Standard  $0.01 \text{ m}^2 / \text{g}$   $0.01 \text{ m}^2 / \text{g}$  Krypton  $0.0005 \text{ m}^2 / \text{g}$   $0.0005 \text{ m}^2 / \text{g}$ .

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com