

**SCOPE OF LEARNING:**

- Hysteresis loss

Technical Specification

- Digital Meter
- Digit Temp. Meter with Control
- Digit Volt Meter
- Digit Ammeter

• AC Power Supply:

- HT power supply (2000Volt) built in the app.
- iFacility to connect CRO provided on the front of the panel.
- Arrangement of sample holder with temperature facility given on the top of the panel.
- 5 nos. of capacitor to control the PE HYSTERESIS CURVE , WHICH ARE INTERNALLY CONNECTED AND CONTROLLED BY THE SLECTOR SWITCH AS GIVEN ON THE TOP OF THE PANEL.
- TEST sample PST and PZT ALSO PROVIDED WITH the apps.
- Control circuit also engraved on lower top panel of the unit.

.SAMPLE TYPE:

1. PST
2. PZT

SALIENT FEATURES:

- Front panel built with high class insulated Printed Circuit Board sheet with well printed circuits and symbols.
- Instruction manual.
- Connections are brought out through 4mm BT15 Terminals.
- The trainer is housed in Wooden cabinet.
- Size of the trainer set 18"x12"

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com