



Technical Specifications :-

- Panel Type: ADS
- Back Light Unit: DLED
- Response Time: 6 ms
- Aspect Ratio: 16:09
- Display Area (H×V): 1428.48 × 803.52 mm
- Pixel Pitch: 0.372 × 0.372 mm
- Resolution: 3840 × 2160
- Refresh Rate: 60 Hz
- Viewing Angle: 178° (H/V)
- Brightness with Glass (Min): 350 cd/m²
- Brightness with Glass (Typ): 400 cd/m²
- Lifetime: ≥ 50,000 Hours
- System Version: Android 13.0
- RAM: 8 GB
- ROM: 128 GB
- Sensing Type: Infrared Recognition
- Touch Recognition: Finger, Passive Stylus

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- Supporting OS (Optional): Windows XP / Android / Linux / Mac OSX / Chrome
- Audio Output: 2 Channels
- Output Power: 2 × 20 W
- Power Supply: 80–240 V ~ 50/60 Hz
- Standby Power: ≤ 0.5 W
- HDMI: 3
- USB 2.0: 1
- USB Player (Media) Type-C: 1
- USB 3.0: 4
- Touch Out: 2
- Audio / Mic In: 1
- Audio Out: 1
- SPDIF: 1
- RS232: 1
- RJ45: 1
- Power Cord: 1
- HDMI Cable: 2
- USB Touch Cable (Type A-B): 1
- Remote Control: 2
- Writing Pen: 1
- Operation Temperature: 0°C ~ 40°C
- Operation Humidity: 10% ~ 90% RH
- Storage Temperature: -20°C ~ 60°C
- Storage Humidity: 10% ~ 90% RH
- Altitude: Below 5000 meters

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com