

**Technical Specifications:**

- CPU: 8086 or higher
- Main RAM: 64 KB (62256 × 2) or higher
- Monitor ROM: 64 KB (27256 × 2) or higher
- Display Unit: LCD (16 × 2 Line)
- I/O Port: 8255a and Serial Port: RS-232C
- System Clock: Minimum 14.7456 MHz
- Dot Matrix LED: 8 × 8 (2 Color)
- Keyboard: Minimum 16 hexadecimal and 10 function keys
- Stepper motor interface and A/D, D/A Converter
- Program download and trace function
- Memory contents modification and dump function
- Sound experiment with Speaker
- Thermistor and Bar LED unit
- Software: 8086 Assembler or as required
- Support C-Language Example Program
- Integrated Development Environment Program for Windows

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- Power source: 220~230V AC, 50Hz, 1 Phase
- Accessories: Software CD, PC interface cable and Instruction manual



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com