



55747 Experimental Set Up has been designed specifically for the Measurement of magnetic susceptibility of paramagnetic solution by Quincke's method. Also find the ionic molecular susceptibility of the ion and magnetic moment of the ion in terms of Bohr magnetron. The set-up consists of Electromagnet, Constant Current Power supply (0 -4Amp), Digital Gauss meter with Hall probe, Traveling microscope, Quincke's tube with stand, sample (FeCl3).

The set up is complete in all respect and requires no other apparatus. Practical experience on this set up carries great educative value for Science and Engineering Students.

#### OBJECT

01 Measurement of magnetic susceptibility of paramagnetic solution by Quincke's method. Also find the ionic molecular susceptibility of the ion and magnetic moment of the ion in terms of Bohr magnetron.

### FEATURES

The complete Experimental Set-up consists of the following :

01 Electromagnet : The electromagnet have the most widely used 'U' shaped softiron yoke. The soft iron is of a special quality, structurally uniform, well machined and finished to meet the rigid standards.

### SPECIFICATIONS

01	Field intensity	:	7.5 KG at 10mm
			airgap which flat
			pole pieces.
	Pole pieces	:	50mm diameter.
	Energising coils	:	Two, each a
			resistance of about
			3.0 ohm.
	Power requirement	:	0-30V dc, 4A, its
			coils are connected
			in series.
02	Constant current	:	
	Current range	:	0 - 4 Amp.
	power supply		
	Load regulation	:	Better than 0.5% of

Note: Specifications are subject to change.

# Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India, Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com Website: www.tesca.in

		the highest Omega type ccp-30/4 (No Load to Full Load) specified output current
Line regulation	:	Better than $\pm 2\%$ of the specified output
Metering	:	Variation) current. 3 ½ digit 7 segment LED DPM.

03 Digital gauss meter :

operates on the principle of Hall Effect in semiconductor. The small Hall Voltage is amplified with hall probe through a high stability amplifier so that millivoltmeter connected at the output of the amplifier Omega type can be calibrated directly in magnetic field unit (Gauss).

## SPECIFICATIONS

Range	:	0.2KG & 0-20KG.	
Resolution	:	1G at 0-2KG range	
Accuracy	:	± 0.5%.	
Special Feature	:	Indicate the direction	
		of the magnetic field.	
Travelling microsco	ope :	: T-shape model with	
		horizontal and vertical	
		scales. The base is	
		fitted with three	
		leveling screws.	
Quin Cke's tube with stand			
Sample - Fecl3 (T	ō be	e managed at your self	
	Range Resolution Accuracy Special Feature Travelling microsco Quin Cke's tube wi Sample - Fecl3 (1	Range : Resolution : Accuracy : Special Feature : Travelling microscope : Quin Cke's tube with s Sample - Fecl3 (To be	

- 06 Sample Fecl3 (To be managed at your self, cannot be supplied)
- 07 Hall probe wooden stand
- 08 Hall probe with Plastic Box
- 09 Weight : 52 Kg. (Approx.)
- 10 Strongly supported by detailed Operating Instructions, giving details of Object, Theory, Design procedures, Report Suggestions and Book References

