



Technical Specifications :	
Form factor	Desktop
Assembly	Wall mounting (incl. screws)
Switching capacity (Gbit/s)	20
MAC address table	8K
Working memory	256 MB
Packet Buffer Memory	512 KB
VLANs	Support for up to 256 VLANs simultaneously (out of 4096 VLAN IDs)
10/100/1000Base-T	8
100/1000Base-T/2500Base-T	-
SFP 1G	2
SFP+ 1G/10G	-
Other interfaces	DC input, on/off switch
PoE power balance	110W
PoE-capable ports	1 to 8
Supported PoE standard	802.3af/802.3at
Max. PoE devices	7 (15.4W) / 3 (30W)
Power supply	150W
Power supply type	External AC/DC adapter
Power supply AC input	100-240 VAC, 50/60Hz, 2.0A
Power supply	150W 54V/2.78A
Efficiency of the mains adapter	100VAC / 1.48A (94.5%) 240VAC / 0.64A (95.9%)
Power consumption	4.86W / 16.57 BTU/hr (idle) 147.1W / 501.6 BTU/hr (full load)
Dimensions width x depth x height	105mm x 240mm x 27mm
Weight	0.636 kg (without packaging) 1.45 kg (with packaging)
Fan	Fanless

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



Order Code -23246844.5
8-Port Switch will full PoE

Operating temperature	0-40°C (operation), -20-70°C (storage)
Humidity	10-90% (operation), 5-90% (storage), non-condensing
Certifications	CB, UL, CE, FCC, ISED, RCM, VCCI, BSMI, NOM / Post GA: Anatel, KC



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

CIN: U29309RJ2011PTC035213
GSTIN: 08AADCT8576E1ZZ

Follow Tescaglobal

