



Key Features

- Front panel built with high class insulated Bakelite sheet with Sticker well printed circuits and symbols.
- The trainer is housed in Modular Based Rack Type Aluminum Extruded Metal cabinet.
- Instruction manual.
- Patch Cords 4mm (Heavy Duty)
- High Voltage Test Points are Provided With 4mm Safety Sockets
- The trainer is housed in Metal cabinet.
- Protection With Emergency Stop.
- Short Circuit protection with the MCB.
- Size of the trainer set 30"x24"

Technical Specifications

Power Supplies:

- DC Power Supply 0-415V AT 4A (External)
- Operated on Mains power 415V, 50Hz $\pm 10\%$

Digital/Analog Meters:

- Voltmeter
- Ammeter
- Wattmeter
- RPM Meter With Proximity Sensor

Components are mounted on the panels are:

- Variac 4A (3Phase)
- Star Delta Starter
- Emergency Stop Switch.

MOTOR SPECIFICATIONS:

- AC Squirrel Cage Ind. Motor 1HP, 415V, AC & 410/960/700/1440 RPM.

SCOPE OF SUPPLY:

- Induction Motor Control Panel
- 3Phase Auto Transformer 4A
- AC Squirrel Cage Ind. Motor 1HP Mounted on Loading Arrangement

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



MOTOR SPECIFICATIONS:

- 3Phase Induction Motor 1HP
- Operating Voltage:415V
- Type: AC
- RPM: 1440 RPM.
- Wattage: 0.75KW
- Terminations: 12 BTI 15 Terminals
- Shaft: Single

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com