


3 5/6 digit 6000 counts Trms LCD Display Auto Ranging, Data Hold, APO, Backlight Temperature, Frequency, Capacitance Diode, Continuity, Resistance, Duty Cycle

Ranges	
DC Voltage	600mV/6V/60V/600V/1000V
Accuracy	± (0.8%+5dgts) on 600mV ± (0.8%+5dgts) on 6V - 600V ± (1.0%+5dgts) on 1000V
AC Voltage	600mV/6V/60V/600V/750V
Accuracy	± (1.2%+8dgts) on 600mV ± (1.2%+6dgts) on 6V - 600V ± (1.2%+8dgts) on 750V
AC Current	60A/600A/1000A
Accuracy	± (2.5%+10dgts) on all ranges
Resistance	600Ω/6KΩ/60KΩ/600KΩ/ 6MΩ/60MΩ
Accuracy	± (1.5%+5dgts) on all ranges
Capacitance	60nF/600nF/6μF/60μF/ 400μF/20mF
Accuracy	± (8.0%+5dgts) on all ranges
Frequency	60Hz/600Hz/6KHz/600KHz/ 6MHz/60MHz
Accuracy	± (1.0%+5dgts) on all ranges
Frequency	50~1KHZ (Thru Clamp)
Accuracy	± (1.5%+5dgts) on all ranges
Temperature	-40°C - 1370°C / 32°F-2000°F
Accuracy	± (1.0%+4dgts) on -40°-1500°C ± (2.0%+3dgts) on 150°-1370°C
Jaw Size	45mm
Power	9V Battery, NEDA 6F22 Type
Low Battery	"  " is indicated
Dimensions	245 x 90 x 45mm (approx.)
Weight	360gms. Incl. Battery (approx.)
Accessories	Test Leads, Carrying Case Operational Manual K-Type Thermocouple Leads



Note: Specifications are subject to change.