

**Specifications -**

Durable, battery-powered lithium polymer battery — tested to last in extreme environments.  
Ergonomic and wearable — doesn't overload you.  
Real-time gas fixations appeared on LCD.  
Bright, wide-point visual alert bars.  
IP68 rating guarantees the most extreme assurance against residue and water — up to 45 minutes at a depth of 1.2 m.  
User-accommodating, carefully designed task with only one button and natural LCD symbols.  
Self-trial of sensors, battery status, circuit uprightness and capable of being heard/visual alerts on startup.  
Compatible with MicroDock II docking station for mechanized knock tests and alignment.  
Compatible with Fleet Manager II software for reporting and fleet management.

**Additional Information -**

- Measuring Parameters - CO, Combustible Gases, H2S, O2
- H2S - 0 to 100 ppm
- Resolution - 1ppm
- CO - 0 to 500 PPM
- Resolution - 1 PPM
- O2 - 0 to 30.0% Vol
- Resolution - 0.1%
- Combustible Gases - 0 to 100% Vol
- Resolution - 1%
- Operating Temperature -20 to +50°C
- Operating Humidity - 0% - 95% RH (non-condensing)

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

- Alarm Visual, vibrating, audible (95 dB) • Low, High, TWA, STEL, OL (over limit)
- Ratings IP67/68
- Tests - Audible/visual alarms on activation; sensors, battery and circuitry (continuous)
- Certifications & Approvals - ATEX , IECEx
- Dimension - 113 X 60 X 31 mm
- Weight - 179 Grams



*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com