

**Technical Specifications :**

- Environment temperature: (-20~70) °C;
- Storage temperature: (-30~80) °C;
- Relative humidity: <95%RH;
- Atmospheric pressure: (86~106) kPa;
- Full-view LCD screen with no blind spots;
- High brightness backlight, easy to read with low illumination;
- 5 digits display with high resolution;
- Dynamic progress bar pressure indication and pressure percentage indication
- Default: ER18505 Lithium battery powered;
- Diameter: head 100mm x 50mm, length 160mm;

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- Thread:M20 x 1.5 G1/2 NPT1/2 (or According to customers' requirements);
- Weight: about 0.5kg;
- Mounting: Bottom. (Back with flange for optional);
- Measuring Range: -100Kpa~100MPa; (Between this range, 11 pressure unit transfer easily.)
- Accuracy Class: $\pm 0.2\%$; $\pm 0.1\%$; $\pm 0.05\%$; $\pm 0.02\%$

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com