



Technical Specifications:

- Have measurement capability of DCV, ACV, DCA, ACA Resistance, Capacitance, Frequency, Diode
- Continuity beeper : Smart operation
- Build in 4 intelligent function: V, Ω , 600A, 1000A
- V function can select ACV, DCV automatically with auto range
- Ω function can select the Resistance, Diode, Continuity beeper, Capacitance automatically with auto range
- Data hold
- Auto shut off is available to save battery life
- 10 M ohm impedance for voltage circuit
- Have built-in overload protection for most ranges
- LSI circuit provides high reliability and durability
- Display: 39.5 mm x29.8 mm large LCD display
- Sampling time: Approx. 0.5 to 1 second
- DC Current, AC Current Range: 600A/1000A
- Resolution: 0.1A /1A
- Accuracy: 600 A Range ($\pm 1.5\%$ +15d)
- 1000 A Range ($\pm 2\%$ +8d)
- Over load protection: AC/DC 1000A
- DC Voltage Range: 600 mV /6 V/60 V/600 V /1000 V

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Resolution: 0.1 mV /0.001V /0.01V /0.1V/1 V
- Accuracy: $\pm (0.8\% + 2600 \text{ mV})$, $\pm (0.8\% + 16 \text{ V}, 60 \text{ V}, 600 \text{ V}, 1000 \text{ V})$
- AC Voltage Range: 6 V/60 V/600 V /1000 V
- Resolution: 0.001V /0.01V /0.1V/1 V
- Accuracy: $\pm (1\% + 2d)$

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com