# BRAKE LATHE FOR HCV/LCV/PCV





# **Technical Specification**

	Processing dia. brake drum	;	180 - 450 mm	
	Processing dia. brake disc	:	≦ 420 mm	
	Rotating speed of work-piece	:	30/52/85 rpm	
	Max. travel of tool	:	170 mm	
	Feeding rate	:	0.16 mm/r	
	Space requirement	:	LxWxH-5x3x5ft	
	NetWeight / GrossWeight	:	320/400 kg	
	Power supply	:	1.1 kW, 3ph	

# Why Brake Lathe

- Over a period of time, brakes in HCV/LCV/PCV undergoes various defects like scoring, cracks and corrosion and affect overall braking performance
- · Brakes can be reassured by means of skimming
- Brake Lathe is used to skim the brake drums and discs in order to increase its life by saving more time
- This ensures additional revenue to the service stations

#### Features & Benefits

- This machine is for repairing the brake drum / disc suitable for all cars and heavy trucks
- · It is a kind of infinitely variable speed lathe
- The brake drum can be skimmed on the first spindle and the brake disc can be skimmed on the second spindle
- This equipment has higher rigidity, accurate work piece positioning
- This equipment is user friendly and easy to operate
- Ensures rigid and effective operation
- · No skilled man power required

#### Suitable For







Disk Brake

Drum Brake

Fly Wheel

# ATS ELGI Ltd.,

Private Industrial Estate, Kurichy, Coimbatore - 641021, India.

Tel: +91-422-2589999 | Email: enquiry@ats-elgi.com

Visit us at: www.ats-elgi.com

Toll-free number: 1800-425-3544

