

**Technical Specifications:-****● Conductivity**

- Range: 0~20.00, 200.0, 2000 μ S/cm, 20.00, 200.0mS/cm (5 auto ranges)
- Accuracy: \pm 1% F.S
- Resolution: 0.01, 0.1, 1
- Calibration Points: up to 3 points
- Conductivity Buffer Option: 10 μ S/cm, 84 μ S/cm, 1413 μ S/cm, 12.88mS/cm, 111.8mS/cm (any three)
- Temperature Compensation: 0~100°C, 32~212°F, Manual or Automatic
- Temperature Coefficient: 0.0~10.0%/°C
- Cell Constant: K=0.1, 1, 10
- Normalization Temperature: 25°C

● TDS

- Range: 0~10 ppt(Max. 200 ppt, depending on factor setting & conductivity range)
- Accuracy: \pm 1% F.S
- TDS Factor: 0.1 to 1.0 (Default 0.5)

● Temperature

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Temperature Range: 0 to 105°C
- Accuracy: $\pm 0.5^{\circ}\text{C}$
- Resolution: 0.1°C
- **General**
- Hold Function: Available
- Auto Off Function: Available
- Connector: 6-pin Mini Plug
- Display: LCD
- Power Supply: DC9V, AC adapters, 220VAC/50Hz
- Dimensions L x W x H: 210 x 205 x 75mm
- Packing Size: 300 x 250 x 175
- Weight: 1.5 kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com