



Picture Shown is only for reference purpose actual product can vary

Description:

Precision cylindrical grinding machine designed for both internal and external grinding applications. Offers high rotational speeds, long travel range, and adjustable orientations for versatile industrial use.

Specifications :

- Height between points: 180 mm
- Distance between centers: 800 mm
- Maximum part diameter: 320 mm
- Maximum rectifiable length: 1000 mm
- Longitudinal travel: 1000 mm
- Grinding wheel stroke: 245 mm
- Table feed: 0.1 to 4 m/min
- Part speed: 6 speeds (300 to 1400 rpm)
- Grinding wheel speed: 10,000 rpm (inside), 1670 rpm (outside)
- Grinding motor power: 5.5 kw
- Spindle motor power: 0.75 kw
- Hydraulic motor power: 0.75 kw
- Engine power lubrication: 0.12 kw
- Spindle orientation to the right: 10°
- Spindle orientation to the left: 90°

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Table orientation: +3° / -7°

Standard Equipment:

- 3-jaw concentric chuck
- 60 mm fixed bezel
- Fixed spindle tip



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com