

**Technical Specifications:**

- "Volume: 9.04 cu. ft. | 256 L
- Interior Dimensions W x H x D in (mm): 25.20" x 31.50" x 19.67" (640 x 800 x 500 mm)
- Exterior Dimensions W x H x D in (mm): 32.44" x 61.10" x 28.90" (824 x 1552 x 734 mm)
- Housing: rear zinc-plated steel Installation: on lockable castors Max. number of internals: 9
- Max. loading of chamber: 440.9 lbs (200 kgs) Max.
- loading per internal: 44.09 lbs (20 kgs)
- Electrical data: 230 Volts: (+/- 10%) 50 Hz / approx. 1350 W
- 115 Volts: (+/- 10%)50/60 Hz / approx. 1350 W
- **Temperature Specs:**
- Setting temperature range: 0 to +50 °C
- Working temperature range with & without humidity: +10°C up to +60°C
- Setting accuracy temperature: 0.1°C
- Temperature sensor: 2 Pt100 sensors DIN Class A in 4-wire-circuit for mutual monitoring, taking over functions in case of an error
- Humidity Specs: Humidity supply with distilled water from external tank by self-priming pump Humidification by hot steam generator Active humidifying and de-humidifying

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

adjustable from 10-80 % rh with digital display of relative humidity

- resolution of display 0.1 %,
- setting accuracy 0.5 % CO2: Digital electronic CO2
- control with automatic zeroing (infrared measuring system)
- adjustment range 0-20 %
- resolution 0.1 %
- CO2-supply via sterile filter Intrinsic adjustment of altitude above sea level CO2
- supply interruption upon door opening”

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com