

SPECIFICATIONS

DC VOLTAGE		
Range	Resolution	Accuracy
200mV	0.1mV	±0.5% of rdg + 4d digits
2V	1mV	
20V	10mV	
200V	100mV	
1000V	1V	±1.0% of rdg + 4d digits

DC CURRENT		
Range	Resolution	Accuracy
200mA	0.1mA	±1.0% of rdg + 5d digits
2000mA	1mA	
20mA	10mA	
200mA	100mA	
2A	1mA	±2.0% of rdg + 5d digits
20A	10mA	

AC VOLTAGE		
Range	Resolution	Accuracy
200mV	0.1 mV	±1.5% of rdg + 15d digits
2V	1 mV	±0.8% of rdg + 6d digits
20V	10mV	
200V	100mV	
750V	1V	± 1.0% of rdg + 6d digits

AC CURRENT		
Range	Resolution	Accuracy
200mA	0.1mA	± 1.5% of rdg + 15d digits
2000mA	1mA	
20mA	10mA	
200mA	100mA	
2A	1mA	±2.0% of rdg + 10d digits
20A	10mA	

RESISTANCE		
Range	Resolution	Accuracy
200W	0.1W	± 0.8% of rdg + 5d digits
2KW	1W	± 1.5% of rdg + 15d digits
20KW	10W	
200KW	100W	
2MW	1KW	+2.0% of rdg + 10d digits
20MW	10KW	

TRANSISTOR hFE TEST		
Range	Test Range	Test Current/Voltage
NPN or PNP	0-1000	Base current is approximate 15pA Vice is about 4.5V

SPECIAL FUNCTION			
Diode and hFE test	✓	Function Protection	✓
Diode and hFE test	✓	Input impedance	10MW
Continuity Buzzer	Approx. < 30 +10	Simpling Rate	3 times per second
Low Battery Diasplay	Approx. < 7.5V	AC Frequency Response	40-400Hz
Auto Power OFF	Approx. 30 min	Power	9V (6F22) X 1

Features

- 3½ Digital Multimeter, 1999 Counts
- Auto Power Off (APO) under natural operation
- Non Contact Voltage (NCV) Test
- Backlight LCD



Standard Accessories : Test Leads, Manual

Dimension : 225(H) x 38(W) x 26(D)mm

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com