

Order Code : 20213570.1
Name : Mortar Penetrometer



Specifications:

IT IS USED FOR FINDING OUT THE RATE OF HARDENING OF MORTAR
SIEVED FROM CONCRETE SPRING AND A STEM GRADUATED FROM 0-70 KG X 1 KG. SIX
INTERCHANGEABLE PENETRATION NEEDLES OF AREAS 645, 323, 65 32 AND 16 MM SQ. IS
PROVIDED . THE PENETRATION RESISTANCE IS MEASURED BY THE FORCE EXERTED TO
PENETRATE THE MORTAR BY 25 MM AND IS INDICATED BY A SLIDING RING ON THE STEM,
WHICH IS GRADUATED. NEEDLE SHANKS ARE MARKED AT EVERY 12.5 MM. SUPPLIED
COMPLETE IN A WOODEN CARRYING CASE.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

TESCA TECHNOLOGIES PVT. LTD.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302029, Rajasthan, India.
Ph/ Fax: 91-141-2771791, 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in