



Overview

The Chipping Spread Rate Test Set is designed to determine the rate of spread of coated chippings on road surfaces, ensuring proper adhesion and uniform distribution of aggregates. The apparatus provides accurate and reliable measurement of bitumen and asphalt chipping spread rates for laboratory and field applications.

Key Features

- Designed for accurate measurement of chipping spread in various operating conditions.
- Lightweight and portable construction for convenient field testing.
- Graduated dipstick for quick and easy spread rate measurement.
- Durable stainless-steel construction for long service life.
- Easy to clean and maintain.
- Suitable for bitumen and asphalt rate of spread determination.

Technical Specifications

Parameter	Specification
Purpose	Determination of coated chipping spread rate on road surfaces
Tray Size	300 mm × 300 mm
Tray Material	Stainless Steel
Capacity	Suitable for measuring volume of chippings required to cover a

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



Parameter	Specification
	standard test area
Measurement Method	Direct reading using graduated dipstick and measuring container
Construction	Durable stainless steel and high-strength materials
Operating Temperature	0°C to 40°C
Weight	Approx. 1.5 kg
Portability	Lightweight design for field use

Standard Supply

- Stainless Steel Test Tray (300 mm × 300 mm)
- Measuring Container
- Graduated Dipstick
- Measuring Scoop
- Calibration Weights
- Carrying Case
- User Manual

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com