



Main Features

- Advanced DDS technology, 25MHz frequency output
- 125MSa/s sample rate, and 32 bits frequency resolution
- Vertical Resolution : 14 bits, 8K arb waveform length
- Comprehensive waveform output : 5 basic waveforms, and 26 built-in arbitrary waveforms
- Comprehensive modulation functions : AM, FM, PM, FSK, PWM, Sweep, and Burst
- Newly supported SCPI
- Newly added frequency counter function
- 3.9 inch high resolution (480 × 320 pixels) TFT LCD display

Specifications

Channel	dual
Frequency Output	25MHz
Sample Rate	125MS/s
Vertical Resolution	14 bits
Waveform	
Standard Waveform	Sine, Square, Pulse, Ramp, and Noise
Arbitrary Waveform	Exponential Rise, Exponential Fall, Sin(x)/x, Step Wave, and others, total 26 built-in waveforms, and other user-defined arbitrary waveforms
Frequency (resolution 32 bits)	
Sine	1 μ Hz - 25MHz
Square	1 μ Hz - 5MHz
Pulse	1 μ Hz - 5MHz
Ramp	1 μ Hz - 1MHz
Noise	25MHz (-3dB) (typical)
Arb	1 μ Hz - 10MHz
Amplitude	
Amplitude	1m Vpp - 10 Vpp (50 Ω), 1m Vpp - 20 Vpp (high impedance)
Resolution	1m Vpp or 14 bits
DC Offset Range (AD+DC)	\pm 5V (50 Ω), \pm 10V (high impedance)
DC Offset Range Resolution	1mV
Load Impedance	50 Ω (typical)
Arbitrary Waveform	
Wave Length	2 pts to 8K pts
Sample Rate	125MS/s
Vertical Resolution	14 bits
Non-volatile Memory	26 waveforms
Modulation	
Modulation Waveform	AM, FM, PM, FSK, Sweep, and Burst
Modulation Frequency	2mHz to 20.00KHz (FSK 1 μ Hz - 100KHz)
Counter	
Function	Frequency Period, +Width, -Width, +Duty, and -Duty
Frequency Range	100mHz - 200MHz
Frequency Resolution	6 digits/s

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

305, Taru Chhaya Nagar, Tonk Road, Jaipur-302029, India
Tel: +91-141-2724326, Mob: +91-9413330765
Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com



Specifications	
Input / Output	
Display	3.9 inch (480 × 320 pixels) TFT LCD
Type	counter, external modulation input / output, external trigger input / output, external reference clock input / output
Communication Interface	USB host, USB device, RS232
Mechanical	
Dimension (W×H×D)	235 × 110 × 295 (mm)
Weight (without package)	3.00 kg

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

305, Taru Chhaya Nagar, Tonk Road, Jaipur-302029, India
Tel: +91-141-2724326, Mob: +91-9413330765
Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com

