

**SPECIFICATIONS:-**

- 5 in 1
- Welding Methods MIG, TIG, MMA, CUT, FCAW
- Power Supply 380/415V
- Frequency 50/60 Hz
- MIG Current Range 40–300A
- MMA Current Range 10–250A
- TIG Current Range 10–250A
- Cutting Current Range 10–100A
- Max Cutting Thickness Up to 25mm
- MIG Wire Diameter 0.6 / 0.8 / 1.0 mm
- Max Electrode Diameter 4.0 mm
- MIG Spool Capacity Up to 15 kg
- Rated Power 12.1 kVA
- Protection Class IP21S
- Insulation Class H
- Power Factor (cosφ) 0.9
- Inductance Adjustment Yes
- 2T/4T Modes Yes
- Non-Touch Pilot Arc Yes
- Overload Protection Yes
- Display Type Digital

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Cooling System Forced Air Cooling
- Dimensions (L×W×H) 450 × 310 × 390 mm
- Weight 38 kg
- Accessories Included TIG torch, MIG torch, plasma torch, electrode holder with cable, ground clamp with cable, water separator with pressure gauge, connecting hose with quick-release **couplings, user manual**

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com