



28558A Mode Characteristics in Fiber Optics experimental setup has been designed to study the mode characteristics of different fiber optic cables. The two basic types of fiber, Single Mode and Multi Mode can be characterized by measuring Numerical Aperture and the Normalized Frequency (V number) parameter, which guides modes that are allowed to propagate in a particular waveguide structure. When $V < 2.405$, only single mode propagates in the wave guide and when $V > 2.405$, the other modes propagate in the wave guide. Using this experimental, the student can easily differentiate between Single Mode and Multi Mode optical fiber cables.

Features

1. Complete set up for Numerical Aperture measurement and V number verification for Single Mode and Multi Mode fiber cables
2. Complete set up for observation of intensity patterns of modes in Single Mode and Multi Mode fiber cables
3. He-Ne LASER Source (650nm; 2mW) with mounting stand and fiber coupler
4. Single Mode & Multi Mode fibers with SMA connectors at each end
5. Numerical Aperture measurement / Mode observation screen with holding assembly
6. Optics bench with fiber coupling assembly and customized mechanical fixtures

Object

1. Measurement of Numerical Aperture and verification of V number of a fiber test cable (Single Mode and Multi Mode)
2. Coupling light into a test fiber cable (Single Mode and Multi Mode) and observing the intensity patterns of modes

Technical Specifications

Optical Source

Source Type	:	He-Ne LASER source.
Wavelength	:	650 nm
Output Power	:	2mW

LASER to fiber coupler

Coupling efficiency	:	>70% for SM fiber > 90% for MM fiber
---------------------	---	---

Single Mode fiber cable

Note: Specifications are subject to change.

Connector type	:	Standard SMA
Cable type	:	Step indexed, Glass cable
Core diameter	:	9 microns
Refractive indices	:	Core: 1.52; Cladding : 1.48
Numerical Aperture	:	0.13
Central wavelength	:	1300 nm to 1600 nm

Multi Mode POF cable

Connector type	:	Standard SMA
Cable type	:	Step indexed, Polymer fiber cable (POF)
Core diameter	:	1000 microns
Refractive indices	:	Core: 1.49; Cladding : 1.42
Numerical Aperture	:	0.5
Central wavelength	:	650 nm to 1300 nm
Fiber length	:	1.0 m
Power Supply	:	110-220V, $\pm 10\%$, 50 / 60 Hz
Power consumption	:	10 VA (approximately)

Dimensions :

LASER Source	:	W 95 x H 110 x D 355 mm
Optics bench	:	W 40 x H 75 x D 500 mm
Weight	:	4 Kg. (approximately)
Operating conditions	:	0-40 C, 85% RH

List of Accessories

1. He-Ne LASER source with mounting stand, Mains cord & Optics bench : 1no
2. Optics bench stands with bolts : 2nos
3. Numerical Aperture measurement / Mode observation screen : 1no
4. NA measurement / Mode observation screen holder with base and screws : 1no
5. Fiber coupling assembly with base and screws : 1no
6. Single Mode fiber optic cable, length 1 meter : 1no
7. Multi Mode fiber optic cable, length 1 meter. : 1no
8. Measuring scale (6 inches) : 1no
9. Plastic box for cables : 1no

Note: Specifications are subject to change.

